	Hits	Search Text	DBs
1	18489	database$1 and partition$4 and @ad < "20030408"	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
2	718	1 and (partition$4 with (id$1 or identifier$1))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
3	27	2 and (partition$4 with schema$1)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
4	26	3 and (quer$4 or inquir$4 or search$4) and stor$4	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
5	7	4 and (database$1 with (catalog$1 or list$1 or director$3 or index$4 or register$4 or log$4 or record$4 or file$1) with partition$4)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
6	7	5 and schema$5	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Hits	Search Text	DBs
7	4	6 and rout$4	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
8	2	7 and table$1	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
9	2	8 and quer$4	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
10	2	7 not 9	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB